

# ZB-80/125/200/330

## bowl cutter series

The cutting machine utilized the cutter rotating with high speed to cut the meat, vegetable, fragrant mushroom, agarics, shallot and ginger etc into the grains with different sizes. The cutting machine produced by our company has the most suitable combination of the cutting speed, pot speed and the distance between the cutter and rotating pot, all these make the cut grains more equal. The back cover of the rotating pot has the rubber bar to prevent the leak, so the material won't leak out during the period of cutting and washing. The axis of cutter has two seals to protect the axletree from being eroded, which can extend the life of the axletree and prevent the drain dropping into the pot and keep the nice lubrication of the rotation place and keep the transmission stable. The seal parts are easy to replace. The distance of the cutter's point and the cutting pot is less than 2mm.

(Model)	Productivity (kg)	Volume (L)	Power (kw)	Knife quantity	Bowl speed (r/min)	Unloader (rpm)(r/min)	Knife (r/min)	Weight (kg)	Dimension (mm)
ZB-80	70-75	80	11	6	7/11	88	750/1500/3000	1300	1900X1500X1500
ZB-125 I	100-110	125	12	6	7/11	88	750/1500/3000	1800	2100X1420X1600
ZB-125 II	100-110	125	33.2	6	7/11	88	300/1500/3000/4500	2000	2100X1420X1600
ZB-200	170-180	200	60	6	7.5/10/15	82	200/1800/3600	3500	2950X2400X1950
ZB-200 (真空Vacuum)	170-180	200	65	6	7.5/10/15	变频调速	200/2100/4200	4800	3100X2420X2300
ZB-330	270-310	330	82	6	6/12	无极调速	200/1800/3600	5000	3855X2900X2100



1. This machine is manufactured with the material of the stainless steel, the structure is tense, and it is good-looking and easy to wash.
2. The main parts adopt the processing center to manufacture so as to guarantee the precision of the processing.
3. Water prevention and human-oriented design, while the operation is simple, the control board can reach IP65 security.
4. The edge of the cutter is sharp and bearing to use, stable when operating with high speed, the material is cut and the emulsification effect is nice.
5. It adopts the imported axletree, while the motor meets the European standard with strong ability of overload resistance.



ZKB-200

